



passive loudspeaker **P5**

LCR - Surround - Height



INTRODUCTION

The P5 delivers the full dynamic range experience to smaller rooms and rooms with multiple surrounds and height speakers. Its compact cabinet can be oriented either vertically or horizontally, even mounted on the ceiling, thanks to its 80 degree circular waveguide and 1" pro compression driver. The P5 comes in semi-matte black or white finish with a magnetically attached removable grille.

TECHNICAL SPECIFICATIONS

| | |
|---------------------------|---|
| Impedance | 8 ohms nominal Phase angles less than 45 degrees |
| Power Handling | |
| Continuous | 75W |
| Peak | 250W |
| Frequency Response | |
| - 3 dB | 90Hz and 20kHz |
| Maximum SPL | |
| free standing | 107dB continuous 113dB peak |
| in wall | 113dB continuous 119dB peak |
| Dispersion pattern | |
| -6dB | Constant directivity 80° circular from 2.5kHz |
| Sensitivity | |
| 1m/1W | 91dB |
| Crossover | Asymmetrical, phase aligned 2.2kHz, BSC |

Components

| | |
|----------------|--|
| Midrange | 5.25" driver with 26mm voice coil in 5 litre sealed box |
| High Frequency | 1" compression driver on a circular constant directivity waveguide |

Connectivity

Gold plated large diameter binding posts

Wall Mount

1 Inserts for VESA 100 bracket and keyholes provided for both vertical and horizontal mounting

Finish

White or Black semi-matte painted finish.

Dimensions

HxWxD

12" x 7.5" x 6.7"
303 x 190 x 170 mm

Shipping Carton

HxWxD

15.35" x 11.4" x 10.25"
390 x 290 x 260 mm

Net weight

10.6 Lbs / 4,8 Kg

Shipping weight

12,3 Lbs / 5, Kg

Assembly

Sweden; 100% QC testing