



passive loudspeaker **P5**

LCR - Surround - Height



INTRODUCTION

The P5 delivers the full dynamic range experience to smaller rooms and rooms with multiple surrounds and height speakers. Its compact cabinet can be oriented either vertically or horizontally, even mounted on the ceiling, thanks to its 80 degree circular waveguide and 1" pro compression driver. The P5 comes in semi-matte black or white finish with a magnetically attached removable grille.

TECHNICAL SPECIFICATIONS

Impedance	8 ohms nominal Phase angles less than 45 degrees
Power Handling Continuous Peak	75W 250W
Frequency Response - 3 dB	90Hz and 20kHz
Maximum SPL free standing in wall	107dB continuous 113dB peak 113dB continuous 119dB peak
Dispersion pattern -6dB	Constant directivity 80° circular from 2.5kHz
Sensitivity 1m/1W	91 dB
Crossover	Asymmetrical, phase aligned 2.2kHz, BSC

Components

Midrange	5.25" driver with 26mm voice coil in 5 litre sealed box
High Frequency	1" compression driver on a circular constant directivity waveguide

Connectivity

Gold plated large diameter binding posts

Wall Mount

1 Inserts for VESA 100 bracket and
keyholes provided for both vertical
and horizontal mounting

Finish

White or Black semi-matte painted finish.

Dimensions

HxWxD
303 x 190 x 170 mm

Shipping Carton

HxWxD
390 x 290 x 260 mm

Net weight

10.6 Lbs / 4,8 Kg

Shipping weight

12,3 Lbs / 5, Kg

Assembly

Sweden; 100% QC testing