



subwoofer

P15

LFE - Balancing



INTRODUCTION

In an astonishingly compact enclosure (just 8.75" / 222mm deep), the P15 subwoofer brings the authority and impact of the mighty P18 to medium and small rooms where nothing less than the best bass quality will do. Its dual 15-inch long-throw Italian pro audio subwoofer drivers have 3" voice coils, and are mounted in a sealed-box heavily-braced enclosure. The P15 is driven by internal amplification with DSP. The P15 blends lightning-quick transient response with massive impact. Capable of 125dB output and able to reproduce bass frequencies in-room flat to 22Hz and below, the P15 is the ideal low-frequency source for mid-sized domestic and professional environments.

TECHNICAL SPECIFICATIONS

Frequency Response	- 3 dB 22 Hz
Maximum SPL @50 Hz	
Continuous	119 dB
Peak	125 dB
Components	Dual long-throw pro audio drivers with cast aluminium chassis and ferrite magnets in 75l sealed box.
DSP section	28 / 56 bit ADI Sigma
DSP settings	free standing, against wall User selectable in corner, baffle wall
Amplifier	2 x 350W, Class-D
Line Voltage	100 - 250V, 40 - 80 Hz
Connectivity	Balanced XLR RCA input adaptor included

Construction

Heavily internally braced MDF, Black painted finish

Dimensions

HxWxD 22.4" x 36.6" x 8.75"

570 x 930 x 222 mm

Shipping Carton

HxWxD 27.2" x 42.5" x 15"

690 x 1080 x 380 mm

Net weight

92 Lbs / 41,7 Kg

Shipping weight

105,2 Lbs / 47,7 Kg (plus pallet)

Included

Damper feet, Power cord
XLR-RCA adaptor

Assembly

Sweden; 100% QC testing