



# subwoofer P10Si Mk2

## LF/P610 Mk2 - Balancing



### INTRODUCTION

The upgraded P10Si Mk2 elevates performance to a higher level compared to the original P10Si, with greater output and low frequency extension. This new version has the same dual applications as a balancing subwoofer and as the low frequency component of the P610 Mk2 full-range loudspeaker.

With a new, higher-performance 10 inch driver in a larger enclosure, the updated Mk2 version's increased output capability improves its performance not only as a balancing subwoofer but as a more capable stand-alone subwoofer. It also completes the full-bandwidth upgrade of the P610 Mk2 when used as the three-way speaker's biamplified woofer element in combination with the P6 Mk2.

### TECHNICAL SPECIFICATIONS

<b>Frequency Response</b>	- 3 dB 26 Hz
<b>Maximum SPL @50 Hz</b>	
Continuous	109 dB
Peak	115 dB
<b>Components</b>	
10 inch long-throw driver with 65mm voice coil	
35 litre sealed box	
<b>Impedance</b>	8 ohms nominal
<b>Power Handling</b>	
Continuous	400W
Peak	1,000W
<b>Sensitivity</b>	
1m/1W	94 dB
<b>Connectivity</b>	gold-plated binding posts
<b>Construction</b>	
Void free MDF, internally cross-braced, Semi-matte paint finish	

<b>Dimensions</b>	18,1" x 18,9" x 8,6"
HxWxD	460 x 480 x 220 mm (rubber feet +12mm)
<b>Shipping Carton</b>	23,6" x 23,6" x 13,8"
HxWxD	600 x 600 x 350 mm
<b>Net weight</b>	55,1 Lbs / 25 Kg
<b>Shipping weight</b>	59,52 Lbs / 27 Kg
<b>Included</b>	Damper feet
<b>Assembly</b>	Sweden; 100% QC testing
<b>Amplification</b>	external amplifier is required
<b>Recommended</b>	One channel of DA03-DSP* or One channel of DA08-DSP*

**Procella amplifiers are sold and packaged separately**  
*\* Amplifier comes with DSP pre-sets for the LF/P610*