



# subwoofer P18Si



## INTRODUCTION

Today's highest-performing systems are designed with multiple subwoofers, and the single 18 inch P18Si recognizes the need for a more compact enclosure that builds on the classic P18 reference subwoofer, delivering the same performance with less output by using the same design and driver.

In fact, the P18Si is exactly one half of the size of the P18, with its smaller enclosure remaining less than a foot in depth! (11.8" / 280mm).

Capable of 127 dB output at 50Hz (133 dB peak), the P18Si is now the subwoofer of choice in systems requiring smaller enclosures, especially when multiple subwoofers are specified and two, three, or four dual-driver P15s or P18s may be too large and/or too costly.

## TECHNICAL SPECIFICATIONS

**Frequency Response** - 3 dB 21 Hz

### Maximum SPL @50 Hz

Continuous 127 dB  
Peak 133 dB

### Components

One long-throw professional 18" driver with 4" voice coil  
Aluminum demodulation ring and Neodymium magnets in  
102 litre sealed box

### Impedance

Driver is 8 ohms nominal

### Power Handling

Continuous 1 x 1,200W  
Peak 1 x 3,000W

### Sensitivity

1m/1W 96 dB

### Connectivity

Gold-plated binding post

### Construction

Heavily internally braced MDF Semi-matte textured black paint finish

### Dimensions

HxWxD 26.4" x 20.6" x 11.8"  
670 x 525 x 280 mm  
(rubber feet +12mm, grill +10mm depth)

### Shipping Carton

HxWxD 31.5" x 23.6" x 15.75"  
800 x 600 x 400 mm

### Net weight

99 Lbs / 45 Kg

### Shipping weight

110 Lbs / 50 Kg (plus pallet)

### Included

Damper feet

### Assembly

Sweden; 100% QC testing

### Amplification

external amplifier is required

### Recommended

One channel of DA08-DSP\*

**Procella amplifiers are sold and packaged separately**

*\*DA08-DSP amplifiers include DSP presets for the P18Si*