



# subwoofer

# P15

## LFE - Balancing



### INTRODUCTION

In an astonishingly compact enclosure (just 8.75" / 222mm deep), the P15 subwoofer brings the authority and impact of the mighty P18 to medium and small rooms where nothing less than the best bass quality will do. Its dual 15-inch long-throw Italian pro audio subwoofer drivers have 3" voice coils and are mounted in a sealed-box heavily-braced enclosure. The P15 is driven by external amplification with DSP.

The P15 blends lightning-quick transient response with massive impact. Capable of 125dB output and able to reproduced bass frequencies in-room flat to 22Hz and below, the P15 is the ideal low-frequency source for mid-sized domestic and professional environments.

### TECHNICAL SPECIFICATIONS

**Frequency Response** - 3 dB 22 Hz

#### Maximum SPL @50 Hz

Continuous 119 dB  
Peak 125 dB

#### Components

Dual long-throw pro audio drivers with cast aluminium chassis and ferrite magnets in 75l sealed box.

#### Impedance

Each driver is 8 ohms nominal

#### Power Handling

Continuous 2 x 800W  
Peak 2 x 1,600W

#### Sensitivity

1m/1W 97 dB

#### Connectivity

Dual gold-plated binding posts One input per driver

#### Construction

Heavily internally braced MDF, Black painted finish

#### Dimensions

22.4" x 36.6" x 8.75"

HxWxD

570 x 930 x 222 mm

#### Shipping Carton

HxWxD

27.2" x 42.5" x 15"

690 x 1080 x 380 mm

#### Net weight

92 Lbs / 41,7 Kg

#### Shipping weight

105 Lbs / 47,7 Kg (plus pallet)

#### Included

Damper feet, Parallel input cables

#### Assembly

Sweden; 100% QC testing

#### External amplification are required

**Procella amplifiers are sold and packaged separately**

**See Tech Sheets for specifications**

#### Recommended amplifier:

- Procella DA03-DSP (2x 280 Watt / 8 Ohm)
- Procella DA08-DSP (1x 800 Watt / 8 Ohm)

Both amplifiers comes with DSP pre-sets for the P15