



subwoofer P15A

LFE - Balancing



INTRODUCTION

Expanding the Procella subwoofer lineup in a slim, compact profile, the P15A is available in both black and white finishes. The 15 inch professional woofer driver features a 3 inch voice coil and cast aluminum chassis. The built in Procella-designed amplifier delivers 350 Watts of class-D power, enabling the subwoofer to deliver 119 dB of output at 50 Hz. For room-shaking low frequencies, the P15A extends down to a -3dB point of 24 Hz. Both XLR and RCA inputs are provided, and switchable room settings optimize the subwoofer's response for room boundary conditions. Thanks to its compact size and slim profile, the P15A is a highly versatile solution. Its performance is outstanding whether in small to medium size rooms or in larger theaters where multiple subwoofers must be accommodated.

TECHNICAL SPECIFICATIONS

Frequency Response	- 3 dB 24 Hz
Maximum SPL @50 Hz	
Continuous	113 dB
Peak	119 dB
Components	
Long-throw 15" driver with 3 inch voice coil and cast aluminum chassis in 55 litre sealed box	
Polarity	Switchable Normal/Reversed
Room Settings	Against wall, In corner
Amplifier	350W, Digital Class D
Connectivity	Single balanced XLR Single RCA input Single RCA output
Line Input	40 - 80 Hz switchable 110 - 240V
Finish	Black or white semi-matte painted finish with matching steel grille

Standby	Programmable
Power Consumption	Standby <0.5W Full Power 440W
Safety Approval	CE, FCC, CCC
Construction	Heavily braced MDF White or Black matte finish matching steel grille
Dimensions	19.875" x 27.5" x 9.65" HxWxD
Shipping Carton	23.5" x 31.5" x 15.35" HxWxD
Net weight	58.4 Lbs / 26.5 Kg
Shipping weight	67 Lbs / 30.5 Kg
Included	Rubber mounting feet, Power cord
Assembly	Sweden; 100% QC testing