



# subwoofer P15A

## LFE - Balancing



### INTRODUCTION

Expanding the Procella subwoofer lineup in a slim, compact profile, the P15A is available in both black and white finishes. The 15 inch professional woofer driver features a 3 inch voice coil and cast aluminum chassis. The built in Procella-designed amplifier delivers 350 Watts of class-D power, enabling the subwoofer to deliver 119 dB of output at 50 Hz. For room-shaking low frequencies, the P15A extends down to a -3dB point of 24 Hz. Both XLR and RCA inputs are provided, and switchable room settings optimize the subwoofer's response for room boundary conditions. Thanks to its compact size and slim profile, the P15A is a highly versatile solution. Its performance is outstanding whether in small to medium size rooms or in larger theaters where multiple subwoofers must be accommodated.

### TECHNICAL SPECIFICATIONS

**Frequency Response** - 3 dB 24 Hz

**Maximum SPL @50 Hz**  
Continuous 113 dB  
Peak 119 dB

**Components**  
Long-throw 15" driver with 3 inch voice coil and cast aluminum chassis in 55 litre sealed box

**Polarity** Switchable Normal/Reversed

**Room Settings** Against wall, In corner

**Amplifier** 350W, Digital Class D

**Connectivity** Single balanced XLR  
Single RCA input  
Single RCA output

**Line Input** 40 - 80 Hz  
switchable 110 - 240V

**Finish** Black or white semi-matte painted finish with matching steel grille

**Standby** Programmable

**Power Consumption** Standby <0.5W  
Full Power 440W

**Safety Approval** CE, FCC, CCC

**Construction** Heavily braced MDF  
White or Black matte finish  
matching steel grille

**Dimensions** 19.875" x 27.5" x 9.65"  
HxWxD 505 x 700 x 245 mm

**Shipping Carton** 23.5" x 31.5" x 15.35"  
HxWxD 595 x 800 x 390 mm

**Net weight** 58.4 Lbs / 26.5 Kg

**Shipping weight** 67 Lbs / 30.5 Kg

**Included** Rubber mounting feet, Power cord

**Assembly** Sweden; 100% QC testing